

# CHRISTIE CAPTIVA DWU500S

Boardrooms | Classrooms | Conference rooms  
Huddle spaces | Museums | Retail

## Maximize your space, captivate your audience

Captivate audiences, inspire creativity, and encourage collaboration with the Christie® Captiva DWU500S 1DLP® ultra short throw laser projector.

Maximize your space without sacrificing visual impact with one of the shortest throw distances available. Easily display WUXGA resolution images up to 12.5' (3.8m) diagonal in landscape or portrait orientations.

With four-corner geometry adjustment, the DWU500S allows you to present flawless images every time, whether you're in the classroom, conference room, or retail environment.

The DWU500S provides 20,000 hours of low-cost and reliable operation, a suite of easy-to-use features, multiple mounting options, and instant on/off, letting you focus on what's important—the content.



**CHRISTIE®**

## Technical specifications

## Christie Captiva DWU500S 171-037101-01, 171-038102-01

Image	brightness (lumens)	<ul style="list-style-type: none"><li>• 4500 ANSI lumens</li><li>• 5000 ISO lumens</li></ul>
	contrast	<ul style="list-style-type: none"><li>• 1800:1 Full on/off</li></ul>
Display technology	type	<ul style="list-style-type: none"><li>• 1-chip 0.67" DMD</li></ul>
	native resolution	<ul style="list-style-type: none"><li>• 1920 x 1200 (2,304,000 pixels) 16:10</li></ul>
	image size (diagonal)	<ul style="list-style-type: none"><li>• 130-150"</li></ul>
Illumination	type	<ul style="list-style-type: none"><li>• Solid-state laser</li></ul>
	typical lifetime	<ul style="list-style-type: none"><li>• 20,000 hrs</li></ul>
Signal inputs	standard	<ul style="list-style-type: none"><li>• HDMI x 2</li><li>• VGA x 1</li><li>• VGA audio in (3.5mm phone jack)</li><li>• Microphone input</li><li>• USB A - for power out only (5V/1.5A)</li></ul>
	max input pixel rate	<ul style="list-style-type: none"><li>• 1600 x 1200 @ 60Hz (162 MHz)</li><li>• 1920 x 1200 @ 60Hz reduced blanking (154 MHz)</li></ul>
	3D	<ul style="list-style-type: none"><li>• Frame packed/side-by-side/top and bottom 3D (HDMI 1.4a)</li><li>• Frame sequential DLP link 3D (VGA/HDMI)</li><li>• Frame sequential DLP link 3D (1024 x 768 @120Hz / 1280 x 720 @120Hz)</li></ul>
	pixel clock	<ul style="list-style-type: none"><li>• 162 MHz</li></ul>
Signal outputs		<ul style="list-style-type: none"><li>• VGA monitor out</li><li>• 10W speaker</li><li>• Audio output (3.5mm phone jack)</li></ul>
Control and networking		<ul style="list-style-type: none"><li>• RS-232 in</li><li>• Ethernet (100BaseT) RJ45</li><li>• Built-in keypad</li><li>• Compatible with Crestron RoomView, AMX, PJ Link</li></ul>
Accessories	standard	<ul style="list-style-type: none"><li>• IR remote</li><li>• AC Line cord for projector head</li></ul>
	optional	<ul style="list-style-type: none"><li>• Wall mount</li></ul>
Lens	adjustment	<ul style="list-style-type: none"><li>• Focus adjustment</li></ul>
	lens	<ul style="list-style-type: none"><li>• 0:25:1 ultra short throw lens</li></ul>
	offsets	<ul style="list-style-type: none"><li>• Fixed offset based on image size</li></ul>
Power requirements	operating voltage	<ul style="list-style-type: none"><li>• 100-240 VAC @ 50/60Hz</li></ul>
	power consumption	<ul style="list-style-type: none"><li>• 350W +/-15% @110V max</li><li>• 250W +/-15% @110V eco mode</li></ul>
	operating current	<ul style="list-style-type: none"><li>• 3.2A +/-15% @110V</li></ul>
	dissipation	<ul style="list-style-type: none"><li>• 1373 BTU/hr max</li><li>• 981 BTU/hr eco mode</li></ul>
Audible noise		<ul style="list-style-type: none"><li>• Standard mode: 36dBA</li><li>• Eco mode: 30dBA</li></ul>
Physical	size	<ul style="list-style-type: none"><li>• (LxWxH) 12.5 x 15.08 x 3.46" (318 x 383 x 88mm) w/o feet</li></ul>
	weight	<ul style="list-style-type: none"><li>• 12.79lbs (5.8kg)</li></ul>
	shipping size	<ul style="list-style-type: none"><li>• (LxWxH) 20.4 x 16.5 x 12.9" (518 x 420 x 328 mm)</li></ul>
	shipping weight	<ul style="list-style-type: none"><li>• 17.2lbs (7.8 kg)</li></ul>
Operating environment	temperature	<ul style="list-style-type: none"><li>• Temp: 40-104°F (5-40°C)</li></ul>
	humidity	<ul style="list-style-type: none"><li>• Humidity: 10-85% non-condensing</li></ul>
Regulatory		<ul style="list-style-type: none"><li>• This product conforms to all relevant European directives, standards, safety, health and environmental concerns</li><li>• Directives: RoHS • REACH • WEEE • UL/CSA/IEC 60950-1 • FCC Class A • CE • CCC • CU • BIS</li></ul>
Warranty		<ul style="list-style-type: none"><li>• 3 years on the projector • 3 years or 20,000 hours on the illumination system<sup>1</sup></li><li>• Contact an authorized Christie representative for full details of our limited warranty</li></ul>

<sup>1</sup> Reference the Christie Standard Limited Warranty document for details.

## Christie support and services

All Christie products are backed by industry-leading warranties, and renowned service and support. We ensure our customers are well-supported with training, service, and technical knowledge through our extensive distribution and support network.

For the most current specification information, please visit [christiedigital.com](http://christiedigital.com)

Copyright 2023 Christie Digital Systems USA, Inc. All rights reserved. Our centers of excellence for manufacturing in Kitchener, Ontario, Canada and in Shenzhen, China are ISO 9001:2015 Quality Management System-certified. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. "Christie" is a trademark of Christie Digital Systems USA, Inc., registered in the United States of America and certain other countries. DLP® and the DLP Logo are registered trademarks of Texas Instruments. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. CD3810-Christie-Captiva-DWU500S-Datasheet-Aug-23-EN

