

CINELIFE+™ SERIES

From boutique cinemas to premium large format auditoriums

Advance cinema storytelling to the next level by bringing the biggest and brightest visual content to life



Key features:

- › **Quick and easy setup** – The auto-configure feature automatically adjusts settings for optimal playback when you connect different sources
- › **Advanced format cinema** – HFR support for 2K and 4K 120fps 2D, 60fps-per-eye 3D playback
- › **Remote UI** – Use a web browser to access the interface anywhere
- › **Hyperrealism** – New system architecture displays content without motion blur or artifacts
- › **Ultra-fast processing** – HDMI 2.0 and 4x 12GB SDI inputs for 1.06G pixels per second
- › **Electronic Color Convergence** – Provides perfect alignment throughout the entire image
- › **Long-lasting light source** – More than 50,000 hours of optimal performance for RGB pure laser models

CHRISTIE
Real|laser™

Advanced laser light source for accurate reproduction of DCI content

CineLife+™

Adds ultra high frame rate providing each eye 2K 120fps, 4K 120fps, 4K 3D 60fps

CINEMA CALCULATOR

Find the right projector and lens for your screen





CP4455-RGB



Premium large format auditoriums |
Advanced format cinema | Event cinema

Operational efficiency: 12.4 lumens per watt

Specifications: Up to 6,000:1 contrast | >95% of Rec. 2020 color gamut | Up to 57,000 lumens with HB lens, 42,000 lumens with UHC lens

Power consumption: 4,630 W including chiller, max DCI brightness, @25°C 15,788 BTU/hr

Dimensions: 61.1x28.0x22.0"
(1551.1x710.6x559.6mm)

Weight: 385lbs (175kg)

Chiller: 26.38x18.5x35.0"
(670x470x890mm); 202lbs (92kg)



CP4445-RGB



Premium large format auditoriums |
Advanced format cinema | Event cinema

Operational efficiency: 11.2 lumens per watt

Specifications: Up to 6,000:1 contrast | >95% of Rec. 2020 color gamut | Up to 47,000 lumens with HB lens, 35,000 lumens with UHC lens

Power consumption: 4,185 W including chiller, max DCI brightness, @25°C 14,271 BTU/hr


Dimensions: 61.1x28.0x22.0"
(1551.1x710.6x559.6mm)

Weight: 385lbs (175kg)

Chiller: 26.38x18.5x35.0"
(670x470x890mm); 202lbs (92kg)



CP4435-RGB



Large-screen auditoriums | Event cinema |
Post production

Operational efficiency: 14.5 lumens per watt

Specifications: Up to 6,000:1 contrast | >95% of Rec. 2020 color gamut | Up to 35,000 lumens

Power consumption: 2,400W, max DCI brightness @ 25°C 8,240 BTU/hr

Dimensions: 37.2x28.0x20.7" (944x711x525mm)

Weight: 285lbs (130kg)



CP4425-RGB



Large-screen auditoriums | Event cinema |
Post production

Operational efficiency: 14.1 lumens per watt

Specifications: Up to 6,000:1 contrast | >95% of Rec. 2020 color gamut | Up to 26,000 lumens

Power consumption: 1,840W, max DCI brightness @ 25°C 6,280 BTU/hr

Dimensions: 37.2x28.0x20.7" (944x711x525mm)

Weight: 285lbs (130kg)



CP4420-RGB



Medium-screen auditoriums | Event cinema
Post production | Screening rooms

Operational efficiency: 12.9 lumens per watt

Specifications: Up to 6,000:1 contrast |
>95% of Rec. 2020 color gamut |
Up to 20,000 lumens

Power consumption: 1555W, max DCI brightness,
@25°C 5305 BTU/hr

Dimensions: 37.2 x 28.0 x 20.7" (944 x 711 x 525mm)

Weight: 238lbs (108kg)



CP4415-RGB



Small-screen auditoriums | Boutique cinema
Post production | Screening rooms

Operational efficiency: 11.9 lumens per watt

Specifications: Up to 6,000:1 contrast |
>95% of Rec. 2020 color gamut |
Up to 15,000 lumens

Power consumption: 1,265W, max DCI brightness,
@25°C 4,320 BTU/hr

Dimensions: 37.2 x 28.0 x 20.7" (944 x 711 x 525mm)

Weight: 238lbs (108kg)



CP2420-RGB



Medium-screen auditoriums | Event cinema
| Post production | Screening rooms

Operational efficiency: 12.9 lumens per watt

Specifications: Up to 6,000:1 contrast | >95% of
Rec. 2020 color gamut | 20,000 lumens

Power consumption: 1,545W, max DCI brightness,
@25C 5,270 BTU/hr

Dimensions: 42.6 x 25.0 x 13.3" (1083x635x337mm)

Weight: 176lbs max (80kg)



CP2415-RGB



Small-screen auditoriums | Boutique cinema
| Post production | Screening rooms

Operational efficiency: 12.7 lumens per watt

Specifications: Up to 6,000:1 contrast | >95% of
Rec. 2020 color gamut | 15,000 lumens

Power consumption: 1,180W, max DCI brightness,
@25C 4,030 BTU/hr

Dimensions: 42.6 x 25.0 x 13.3" (1083x635x337mm)

Weight: 174lbs max (79kg)



CP4420-Xe



Medium-screen auditoriums | Event cinema
Post production | Screening rooms

Specifications: 2,000:1 contrast | DCI-P3 color
| Up to 22,000 lumens

Power consumption: max DCI brightness @25°C
15,350 BTU/hr

Dimensions: 41.9" x 25.4" x 17.5"
(1064 x 644 x 446mm)

Weight: 256lbs max (116kg)



CP2420-Xe



Medium-screen auditoriums | Event cinema
Post production | Screening rooms

Specifications: >2,000:1 contrast | DCI-P3 color
| Up to 22,000 lumens

Power consumption: max DCI brightness @25°C
15,350 BTU/hr max

Dimensions: 41.9" x 25.4" x 17.5"
(1064 x 644 x 446mm)

Weight: 256lbs max (116kg)



CP2415-Xe



Small-screen auditoriums | Boutique cinema
Post production | Screening rooms

Specifications: 2,000:1 contrast | DCI-P3 color
| Up to 15,000 lumens

Power consumption: max DCI brightness @25°C
10,920 BTU/hr

Dimensions: 27 x 25 x 15" (687x665x395mm)

Weight: 122lbs max (55kg)

Corporate offices

Christie Digital Systems USA, Inc.
Cypress
PH: +1 714-236-8610
Christie Digital Systems Canada
Inc.
Kitchener
PH: +1 519-744-8005

Worldwide offices

Australia
PH: +61 (0) 7 3624 4888
Brazil
PH: +55 11 3181-2952
China (Beijing)
PH: +86 10 6561 0240
China (Shanghai)
PH: +86 21 6030 0500

China (Shenzhen)
PH: + 86 755 3680 7000
Colombia
PH: +57 (315) 652-9620
Germany
PH: +49 221 99 512-0
India
PH: +91 (080) 6708 9999

Mexico
PH: +52 (55) 4744-1791
Singapore
PH: +65 6877 8737
South Korea
PH: +82 2 702 1601
Spain
PH: +34 (0) 91 633 99 90

United Arab Emirates
PH: +971 (0) 4 503 6800
United Kingdom
PH: +44 (0) 118 977 8000
United States (Arizona)
PH: +1 602-943-5700
United States (Texas)
PH: +1 469-757-4420

For the most current specification information, please visit christiedigital.com

Copyright 2023 Christie Digital Systems USA, Inc. All rights reserved. Our centers of excellence for manufacturing in Kitchener, Ontario, Canada and in Shenzhen, China are ISO 9001:2015 Quality Management System-certified. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. "Christie" is a trademark of Christie Digital Systems USA, Inc., registered in the United States of America and certain other countries. DLP® and the DLP logo are registered trademarks of Texas Instruments. Performance specifications are typical. Due to constant research, specifications are subject to change without notice.
CD4191-CineLife+ -line-card-Jan-24-EN

