

CHRISTIE SECURE SERIES LCD PANELS

4K UHD LCD panels for secure operations

The Christie® Secure Series is a line of specialized LCD panels for high-security environments. Available in a range of sizes, these displays are perfect for meeting rooms, lobbies, digital signage and more.

The Secure Series comprises a range of TAA-compliant, non-RF LCD panels with no integrated hard drive designed specifically for secure-facility applications typically found in government, corporate and military environments. The Secure Series includes professional features such as OPS slot, UHD resolution, touch interactivity options, and USB playback in a secure, reliable and affordable package.



- › Available sizes: 55", 65", 75", 86" and 98"
- › Non-RF for increased security
- › TAA-compliant
- › Crestron Connected for seamless integration onto a Crestron network
- › Touch interactivity with select models
- › 4K UHD resolution and direct-lit LED for impeccable image quality
- › Feature-rich at an affordable price point
- › OPS slot for increased flexibility and integration ease
- › Brightness of 400 nits or more
- › Landscape and portrait orientations (some models)
- › Backed by Christie support, service and 3 years parts and labor limited warranties



CHRISTIE®

Technical specifications		SUHD551-L	SUHD651-L	SUHD751-P	SUHD861-P	SUHD983-P	
Display technology	screen size (diagonal)	• 55"/139.7cm	• 65"/165.1cm	• 75"/190.5cm	• 86"/217.4cm	• 98"/247.7cm	
	native resolution	• UHD 3840 x 2160 (16:9)					
	backlight	• Direct-lit LED					
	LED lifespan	• 50,000 hours to 50% brightness					
	display orientation	• Landscape			• Portrait or landscape		
	pixel pitch	• 0.315 x 0.315mm	• 0.372 x 0.372mm	• 0.429 x 0.429mm	• 0.493 x 0.493mm	• 0.57 x 0.57mm	
	nominal bezel size (bottom/side/top)	• 14mm/11mm/11mm	• 21mm/15mm/15mm	• 20mm/13mm/13mm	• 38mm/38mm/38mm	• 16mm/16mm/16mm	
	brightness	• 400 nits (cd/m ²) typical			• 600 nits (cd/m ²) typical	• 500 nits (cd/m ²) typical	
	contrast ratio (full field)	• 1200:1 typical	• 4000:1 typical	• 1200:1 typical			
	viewing angle (CR 10:1)	• 178° h/v					
	refresh rate	• 60Hz					• 120Hz
	response time	• 8ms typical					
	color space (CIE 1931)	• 68% typical	• 75% typical	• 68% typical	• 72% typical		
	display colors	• 10 bit, 1.07 billion colors					
Video	inputs	• 2 x HDMI (Ver 2.0, HDCP 2.2) • DisplayPort (Ver 1.2a, HDCP 1.3, supports a UHD signal at 30Hz only)				• 4 x HDMI (Ver 2.0b, HDCP 2.2) • DisplayPort Ver 1.4 • OPS	
	outputs	• VGA • YPbPr • USB 3.0 • 2 x USB 2.0				• DisplayPort 1.2a; HDMI 2.0	• None
Audio	inputs	• RCA (L/R) line in				• 3.5mm headphone jack	
	outputs	• RCA (L/R) line out • 3.5mm headphone jack • SPDIF coax				• 3.5mm headphone jack	
Control	inputs	• RS-232 (D-Sub9) • LAN (RJ45) • IR wire extender				• RS-232 (D-Sub9) • LAN (RJ45) • IR wire extender • USB-A2.0 for service	
Power	input rating	• 100-240 VAC @ 50-60Hz				• 110-240 VAC @50-60Hz	
	power consumption	• 70W typical without OPS • 140W maximum without OPS • <=0.5W in standby without OPS	• 73W typical without OPS • 140W maximum without OPS • <=0.5W in standby without OPS	• 218W typical without OPS • 250W maximum without OPS • <=0.5W in standby without OPS	• 251W typical without OPS • 310W maximum without OPS • <=0.5W in standby without OPS	• 600W maximum without OPS • <=0.5W in standby without OPS	
Environment	operating temperature	• 32-104°F (0-40°C)					
	storage temperature	• -4-140°F (-20-60°C)					
	operating humidity	• 20-90% RH non-condensing					
Physical	size (panel only) (WxHxD)	• 48.7 x 28 x 4.1" (1238 x 712 x 104mm)	• 57.4 x 33.1 x 3.8" (1459 x 841 x 96mm)	• 66.3 x 38.1 x 2.8" (1684 x 967 x 73mm)	• 77.8 x 45.1 x 4.1" (1975 x 1146 x 103mm)	• 86.4 x 49.2 x 4.8" (2194 X 1249.1 X 95.5mm)	
	weight	• 38.6lbs (17.5kg)	• 54.5lbs (24.7kg)	• 80.5lbs (36.5 kg)	• 144.4lbs (65.5 kg)	• 209.4lbs (95 kg)	
	mounting	• VESA 400 x 200mm, M6			• VESA 600 x 400mm, M6		• VESA 800 x 400mm, M8
Runtime	• Designed for 16/7 operation featuring a reliable power supply ¹			• Designed for 24/7 operation featuring a reliable power supply ¹			
Features	• Commercial-grade LCD with LED backlight • OPS slot • Anti-glare treatment • 2 x 8W speakers • On/off scheduler • USB playback of Photo/Video/MP3 • HDMI-CEC • Source switching for failover • Kensington lock • Pixel shifting • No RF capability • Crestron Connected 2				• Commercial-grade LCD with LED backlight • OPS slot • Anti-glare treatment • 2 x 15W speakers • HDMI-CEC • Source switching for failover • No RF capability • 4 window multi-source UHD viewing (Quadview, PiP, PBP) • MEMC • Crestron Connected 2		
Accessories	• Panel ships with IR remote control • External IR receiver • Power cable • User manual					• Optional touch overlay with up to 10 point IR touch ²	
Warranty	• Three years parts and labor limited warranty • Contact an authorized Christie representative for full details						

¹ Avoid static images for extended periods. Refer to the user manual for additional runtime guidelines.

² Content and operating conditions can affect the useful life of the product.

³ Certain models only

Please refer to the product user manual and Christie Operating Guidelines for Flat Panels, available at www.christiedigital.com

Service and support

All our LCD panels come standard with a 3-year commercial warranty. For added peace of mind and to maximize uptime, we offer advanced exchange or on-site repairs during the first year of your warranty.

For the most current specification information, please visit christiedigital.com

Copyright 2023 Christie Digital Systems USA, Inc. All rights reserved. Our centers of excellence for manufacturing in Kitchener, Ontario, Canada and in Shenzhen, China are ISO 9001:2015 Quality Management System-certified. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. "Christie" is a trademark of Christie Digital Systems USA, Inc., registered in the United States of America and certain other countries. DLP® and the DLP logo are registered trademarks of Texas Instruments. Performance specifications are typical. Due to constant research, specifications are subject to change without notice.
CD3961-Christie-Secure-Series-DataSheet-Oct-23-EN

CHRISTIE®